08/12/2009 14:38

RECEIVED CENTRAL FAX CENTER

DEC 0 8 2009

S/N 10/584219 Response to Office Action dated June 8, 2009

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

HSML

Listing of Claims:

- 1. (Currently Amended) A method of raising <u>a</u> temperature of an object contained hermetically in a container to a predetermined temperature, the method comprising:
- a first step for of measuring a temperature of the container and an ambient temperature around the container;
- a second step <u>for of</u> determining an amount of heat energy necessary for raising the temperature of the contained object up to the predetermined temperature, the determination being based on the container temperature and the ambient temperature; and
- a third step for of supplying heat energy to the container, based on a result of the second step.
- 2. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 1, wherein the container comprises a receptacle having an opening and a seal for sealing the opening,

wherein the measurement of the container temperature in the first step is performed at the seal.

3. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 1, further comprising a fourth step, performed between the first step and the second step, for <u>of</u> estimating temperature of the contained object based on the container temperature and the ambient temperature,

wherein in the second step, the estimated temperature is checked to be higher or lower than an additional predetermined temperature set lower than said predetermined temperature, and wherein the amount of heat energy to be supplied to the container is determined based on the check result.

S/N 10/584219 Response to Office Action dated June 8, 2009

- 4. (Currently Amended) The method of raising a temperature of a contained object according to claim 3, wherein in the second step, the amount of heat energy to be supplied to the container is determined so that the amount of heat energy to be supplied to the container per unit time is smaller when the estimated temperature is higher than the additional predetermined temperature, than when the estimated temperature is lower than the additional predetermined temperature.
- 5. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 3, wherein in the fourth step, the estimated temperature is calculated based on a pre-examined correlation between an object-container temperature difference when a predetermined time passes from the beginning of temperature raising and the ambient temperature when the predetermined time passes.
- 6. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 5, wherein the predetermined time is set for an initial stage of raising the temperature of the contained object up to the predetermined temperature where a temperature rising rate of the contained object and the container per unit time is relatively large.
- 7. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 6, wherein the predetermined time is set at a value selected from a range of 10 seconds to 2 minutes after the beginning of <u>the</u> temperature raising.
- 8. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 1, wherein in the third step, the container is brought into contact with a heat medium, and control of the amount of heat energy to be supplied to the container is performed by controlling the temperature of the heat medium.
- 9. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 8, wherein the heat medium is a heating block.

S/N 10/584219
Response to Office Action dated June 8, 2009

- 10. (Currently Amended) A method of raising <u>a</u> temperature of <u>a</u> contained object sealed in a container, up to a predetermined temperature, by supplying heat energy to the container brought into contact with a heating block, the method comprising:
- a first step for of measuring ambient temperature around the container immediately before raising the temperature;
- a second step for of determining an amount of heat energy necessary for raising the temperature of the contained object up to the predetermined temperature, based on the ambient temperature; and
- a third step for of supplying heat energy to the container via the heating block, based on a result of the second step.
- 11. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 10, wherein in the second step, the amount of heat energy to be supplied to the container is controlled by setting <u>a</u> temperature of the heating block and setting <u>a</u> time for which that the set temperature of the heating block is to be maintained.
- 12. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 10, wherein in the second step, supplying the supplied time of the heat energy is divided into a first period from <u>a</u> beginning of the supply of the heat energy until a predetermined time passes, and a second period from the <u>an</u> end of the predetermined time until the supply of the heat energy ends,

wherein the amount of heat energy to be supplied to the container is regulated so that the amount of heat energy to be supplied per unit time is smaller in the second period than in the first period.

13. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 10, wherein in the second step, the amount of heat energy necessary for raising the temperature of the contained object up to the predetermined temperature is calculated based on a pre-examined correlation,

wherein the correlation is a difference between the temperatures of the contained object and the container measured when a predetermined time passes after the beginning

S/N 10/584219
Response to Office Action dated June 8, 2009

of <u>the</u> temperature raising, with the ambient temperature measured when a predetermined time passes after the beginning of <u>the</u> temperature raising, the predetermined time being set within <u>an</u> initial stage of raising the temperature of the contained object up to the predetermined temperature where the temperature rising amount of the contained object and the container per unit time is relatively large.

14. (Currently Amended) The method of raising <u>a</u> temperature of <u>a</u> contained object according to claim 10 13, wherein the predetermined time is set at a value selected from a range of 10 seconds to 2 minutes after the beginning of <u>the</u> temperature raising.

15-23. (Canceled)